



One-piece easy to open bonnet



Available also with front 4WD axle

AGROLUX

4.80 / 60

ROBUST AND RELIABLE.

AGROLUX 4.80 / 60

An extraordinarily agile, versatile and simple to use tractor.

► The Agrolux series is powered by SDF 1000 Tier II engines, offered in either a compact three-cylinder configuration for maximum agility, or in a four-cylinder configuration for maximum tractive performance. These SDF engines are robust, compact and combine ready power delivery even at low engine speeds with outstanding fuel economy.

●: standard ○: optional -: not available

The technical data and pictures are guideline only. Committed to delivering a product more and more in line with your needs, DEUTZ-FAHR reserves the right to update the specifications of its machines at any time.

MACHINE SPECIFICATIONS		AGROLUX 4.80	AGROLUX 60
ENGINE			
Manufacturer		SDF	SDF
Model		1000.4W	1000.3 W
Emissions		Stage II	Stage II
Cylinders/Displacement	n°/cc	4/4000	3/3000
Intake		Naturally aspirated	Naturally aspirated
Max. power	kW/HP	54.4/74	40.5/55
Maximum torque	Nm	270	185
Air filter with dust ejector		○	○
Fuel tank capacity	litres	70	70
TRANSMISSION			
Number of speeds		12+3	12+3
Number of speeds with supercreeper gear		-	-
Minimum speed with supercreeper gear	km/h	0.77	0.77
Maximum speed	km/h	30	30
PTO			
Rear PTO	rpm	540/540ECO	540/540ECO
Ground speed PTO		-	-
AXLES AND BRAKES			
2WD equipment		○	○
4WD front axle with brakes		●	●
Front wheel drive engagement		Mechanical	Mechanical
Front and rear differential lock engagement		Mechanical	Mechanical
Hydrostatic steering with independent pump		●	●
HYDRAULIC SYSTEM AND LIFT			
Fixed displacement pump flow (standard/optional)	l/min	42	33
Auxiliary rear mechanical distributors	n°	1/2/3	1/2
Rear lift control (Mechanical/Easy Lift)		●/-	●/-
Rear lift capacity	kg	2250	2250
DRIVING POSITION			
Platform		Straddle	Straddle
Side mounted levers		●	●
ROPS		○	○
DIMENSIONS AND WEIGHTS			
Width (min.-max.)	mm	1985-2285	1969-2269
Wheelbase (4WD/2WD)	mm	2105/2160	1975/2037
Total unladen weight (min.-max.)	kg	2420-2820	2420-2550