

PE·VO·LON® product overview

PEVOLON®

WHEELS AND CASTORS

PEVOLON® is a thermoplastic material based on polyamide. PEVOLON® wheels have high abrasion resistance, a low friction coefficient, high load capacities and a long lifespan.

The precise workmanship guarantees the functionality of swivel and fixed castor housings. Compact brake systems offer long-lasting, secure locking for all areas of application. The dimensions fulfil to the standards of the European manufacturers of castors.



Series A
70 - 2.000 kg
Page 36 - 37



Series PAG
1.000 - 50.000 kg
Page 38



Series B
150 - 1.000 kg
Page 39



Series 86 HH
100 - 125 kg
Page 39



Series PL/PB
75 - 400 kg
Page 41 - 42



Series WL/WB
300 - 1.400 kg
Page 43



Series TL/TB
600 - 1.000 kg
Page 44



Series ULC/UBC
700 - 2.000 kg
Page 45



Series ULCD/UBCD
1.100 - 20.000 kg
Page 46










Series UL PAG
Series UB PAG
1.750 - 12.000 kg
Page 47











PEVOLON® wheels with plain bearing

High-quality thermoplastic polyamide. Wheels in heavy-duty design with maintenance-free plain bearing (/1).

						
Article code	mm	mm	mm	mm	mm	kg
A 040/033/1/10	40	33	35	17	10	80
A 045/019/1/10	45	19	22	16	10	70
A 050/017/1/10-1	50	17	20	26	10	150
A 050/017/1/10-2	50	17	19	20	10	140
A 050/019/1/06	50	19	27	13	06	100
A 050/025/1/10	50	25	30	18	10	150
A 060/020/1/10	60	20	25	20	10	150
A 065/030/1/10	65	30	35	20	10	170
A 070/030/1/10	70	30	40	25	10	200
A 075/023/1/15	75	23	25	30	15	200
A 080/035/1/15	80	35	37	30	15	300
A 080/035/1/20	80	35	35	50	20	300
A 100/030/1/10	100	30	40	35	10	300
A 100/040/1/15	100	40	50	48	15	450
A 100/050/1/15	100	50	60	55	15	600
A 125/040/1/15	125	40	53	60	15	600
A 125/050/1/15	125	50	60	56	15	700
A 125/050/1/20	125	50	60	56	20	700
A 150/040/1/15	150	40	50	35	15	450
A 150/040/1/20	150	40	53	65	20	700
A 150/050/1/20-1	150	50	55	65	20	600
A 150/050/1/20-2	150	50	60	62	20	800
A 160/050/1/20	160	50	60	63	20	850
A 175/040/1/20	175	40	57	65	20	800
A 175/050/1/20	175	50	55	65	20	750
A 200/040/1/15	200	40	50	45	15	750
A 200/040/1/20	200	40	58	65	20	1.000
A 200/050/1/20-1	200	50	55	65	20	1.000
A 200/050/1/20-2	200	50	60	65	20	1.200
A 200/050/1/25	200	50	60	65	25	1.200
A 250/050/1/20	250	50	60	65	20	1.500
A 250/050/1/25	250	50	60	65	25	1.500
A 250/060/1/25	250	60	65	90	25	1.500
A 300/060/1/30	300	60	70	92	30	2.000



							
Article code	mm	mm	mm	mm	mm	mm	kg
A 080/035/5/12	80	35	35	33	50	12	300
A 100/040/5/12	100	40	50	43	48	12	450
A 100/040/5/17	100	40	50	50	48	17	450
A 100/050/5/20	100	50	60	60	55	20	600
A 120/050/5/20	120	50	58	56	58	20	600
A 125/040/5/20	125	40	53	53	60	20	600
A 125/050/5/20	125	50	60	62	70	20	700
A 150/040/5/20	150	40	53	51	65	20	700
A 150/050/5/12	150	50	55	60	65	15	600
A 150/050/5/20-1	150	50	55	53	65	20	600
A 150/050/5/20-2	150	50	60	62	76	20	800
A 160/040/5/20	160	40	60	58	60	20	600
A 175/050/5/20	175	50	55	53	65	20	800
A 200/050/5/12	200	50	55	60	65	15	1.000
A 200/050/5/20	200	50	60	60	85	20	1.200
A 200/065/5/25	200	65	74	72	80	25	1.300
A 250/050/5/25	250	50	60	60	92	25	1.500
A 250/060/5/25	250	60	65	63	90	25	1.500
A 300/060/5/25	300	60	70	68	92	25	2.000

PEVOLON® wheels with ball bearings

High-quality thermoplastic polyamide. Wheels in heavy-duty design with ball bearings (/5).








PE·VO·LON® heavy-duty wheels

Series PAG



PEVOLON® heavy-duty wheels

High-quality thermoplastic polyamide. Wheels in extra heavy-duty design made of hard and tough, highly compressed cast polyamide with ball bearings (/5) or spherical roller bearings (/3).

							
Article code	mm	mm	mm	mm	mm	mm	kg
PAG 080/040/5/20 B	80	40	45	45	65	20	1.000
PAG 100/040/5/20 B	100	40	45	45	65	20	1.250
PAG 125/055/5/25 B	125	55	60	60	80	25	2.000
PAG 150/055/5/30 B	150	55	60	60	95	30	2.500
PAG 150/080/5/35 B	150	80	90	90	100	35	3.000
PAG 200/055/5/35 B	200	55	60	60	100	35	3.000
PAG 200/080/5/45 B	200	80	90	90	120	45	4.500
PAG 250/065/5/45 B	250	65	70	70	120	45	5.000
PAG 250/080/5/50 B	250	80	90	90	130	50	6.000
PAG 300/080/5/55 B	300	80	90	90	150	55	7.000
PAG 300/110/5/70 B	300	110	120	120	180	70	10.000
PAG 400/110/5/80 B	400	110	120	120	210	80	12.000
PAG 500/130/5/100 B	500	130	130	130	–	100	15.000
PAG 600/150/3/100 B	600	150	165	170	300	100	21.000
PAG 700/200/3/130 B	700	200	215	220	300	130	30.000
PAG 1000/330/3/160 B	1000	330	345	350	400	160	50.000

PEVOLON® • PEVOPLAST®
PEVOTHAN®

Solid rubber
wheels and castors

Electrically conductive
wheels and castors

VULKOLAN® • PEVOPIR®
PEVDYN® / Soft

Stainless steel castors

Institutional
wheels and castors

Conveyor/guiding
rollers and tail units

Profile rollers

Pallet rollers

Press-on tyres

PE·VO·LON® wheels

heat-resistant wheels

Series 86 HH

Series B



Article code	mm	mm	mm	mm	mm	kg
B 080/030/1/10	80	30	35	18	10	150
B 080/035/1/12	80	35	40	20	12	150
B 100/034/1/10	100	34	40	25	10	200
B 100/034/1/12	100	34	40	25	12	200
B 108/035/1/10	108	35	40	25	10	200
B 125/040/1/15	125	40	50	30	15	300
B 150/042/1/15	150	42	50	40	15	600
B 150/042/1/20	150	42	50	38	20	400
B 160/040/1/15	160	40	50	30	15	400
B 175/050/1/15	175	50	55	35	15	425
B 175/050/1/20	175	50	60	45	20	425
B 200/040/1/15	200	40	50	45	15	800
B 200/040/1/20	200	40	50	45	20	450
B 200/050/1/15	200	50	55	35	15	450
B 200/050/1/20	200	50	60	50	20	500
B 250/050/1/20	250	50	60	50	20	1.000

Article code	mm	mm	mm	mm	mm	kg
86 HH 070/035/1/12	70	35	40	30	12	100
86 HH 080/035/1/10	80	35	40	30	10	100
86 HH 100/035/1/10	100	35	40	35	10	125
86 HH 100/035/1/10	100	35	37	35	10	125

Swivel- and fixed castors with wheels series 86 HH and heat-resistant solid rubber wheels available on request.

PEVOLON® wheels

High-quality thermoplastic polyamide. Wheels in light-duty design with maintenance-free plain bearing (/1).

Heat-resistant wheels

Wheels made of phenolic resin with plain bearing (/1). Temperature-resistant from -40° C up to +230° C.

PEVOLON® - PEVOLASTIC®
PEVOTHAN®

Solid rubber
wheels and castors

Electrically conductive
wheels and castors

VULKOLLAN® - PEVOPIUR®
PEVODYN® / Soft

Stainless steel castors

Institutional
wheels and castors

Conveyor/guiding
rollers and ball units

Profile rollers

Pallet rollers

Press-on tyres

PE•VO•LON® castors



PEVOLO® • PEVOUSTIC® PEVOTHAN®	Solid rubber wheels and castors	Electrically conductive wheels and castors	VULKOLLAN® • PEVOPIUR® PEVODYN® / -Soft	Stainless steel castors	Institutional wheels and castors	Conveyor/guiding rollers and ball units	Profile rollers	Pallet rollers	Press-on tyres
-----------------------------------	------------------------------------	---	--	-------------------------	-------------------------------------	--	-----------------	----------------	----------------

PE·VO·LON® industrial castors



Series PB/1

Series PL/1


Article code	mm	mm	mm	mm	mm	mm	mm	kg
PL 050/25/1	50	25	72	80 x 60	60 x 40	7	21	75
PL 070/30/1 L	70	30	103	105 x 85	80 x 60	9	38	120
PL 080/30/1 L	80	30	108	105 x 85	80 x 60	9	38	120
PL 100/34/1 L	100	34	128	105 x 85	80 x 60	9	38	125
PL 100/40/1	100	40	126	135 x 110	105 x 80	11	40	300
PL 125/40/1 L	125	40	155	105 x 85	80 x 60	9	45	180
PL 125/40/1	125	40	164	135 x 110	105 x 80	11	55	300
PL 150/42/1	150	42	194	135 x 110	105 x 80	11	55	300
PL 175/50/1	175	50	217	135 x 110	105 x 80	11	55	350
PL 200/50/1	200	50	239	135 x 110	105 x 80	11	55	400
PL 250/50/1	250	50	290	135 x 110	105 x 80	11	55	400

Industrial swivel castors with PEVOLON® wheels

Wheels series A/B with plain bearing (/1), see page 36/39.

Article code	mm	mm	mm	mm	mm	mm	mm	kg
PB 050/25/1	50	25	72	93 x 50	71 x 24	6	75	
PB 070/30/1 L	70	30	103	105 x 85	80 x 60	9	120	
PB 080/30/1 L	80	30	108	105 x 85	80 x 60	9	120	
PB 100/34/1 L	100	34	128	105 x 85	80 x 60	9	125	
PB 100/40/1	100	40	126	135 x 110	105 x 80	11	300	
PB 125/40/1	125	40	164	135 x 110	105 x 80	11	300	
PB 125/40/1 L	125	40	155	105 x 85	80 x 60	9	180	
PB 150/42/1	150	42	194	135 x 110	105 x 80	11	300	
PB 175/50/1	175	50	217	135 x 110	105 x 80	11	350	
PB 200/50/1	200	50	239	135 x 110	105 x 80	11	400	
PB 250/50/1	250	50	290	135 x 110	105 x 80	11	400	

Industrial fixed castors



Industrial swivel castor brackets with a load capacity of up to 400 kg

Housings made of pressed steel, zinc and chromated. Swivel head with double ball bearings, dust and splash proof, with riveted kingpin. ALLSTOP total locking device on the trailing side of the housing, blocks rolling and swivel motion simultaneously.

* with locking device code: PLFZ...

ALLSTOP total locking device Code: PLF...	single bolt hole Code: PL...R	single bolt hole/total lock Code: PLF...R
directional lock Code: PL.../...TRIF	foot protection Code: ...PRO	stem fitting Code: PLZ...*

PEVOLON® - PEVOLOSTIC®
PEVOTHAN®

Solid rubber
wheels and castors

Electrically conductive
wheels and castors

VULKOLLAN® - PEVOPIUR®
PEVODIN® / Soft

Stainless steel castors

Institutional
wheels and castors

Conveyor/guiding
rollers and ball units

Profile rollers

Pallet rollers


Press-on tyres

PE·VO·LON® industrial castors










Series PB/3

Series PL/3


									
Article code	mm	mm	mm	mm	mm	mm	mm	mm	kg
PL 100/34/3 L	100	34	128	105 x 85	80 x 60	9	38	125	
PL 125/40/3 L	125	40	155	105 x 85	80 x 60	9	45	150	
PL 125/40/3	125	40	164	135 x 110	105 x 80	11	55	250	
PL 150/42/3	150	42	194	135 x 110	105 x 80	11	55	300	
PL 200/50/3	200	50	239	135 x 110	105 x 80	11	55	400	
PL 100/40/5	100	40	126	135 x 110	105 x 80	11	40	300	
PL 125/40/5	125	40	164	135 x 110	105 x 80	11	55	300	
PL 150/50/5	150	50	194	135 x 110	105 x 80	11	55	400	
PL 200/50/5	200	50	239	135 x 110	105 x 80	11	55	400	
PL 250/50/5	250	50	290	135 x 110	105 x 80	11	55	400	

Industrial swivel castors with PEVOLON® wheels

Wheels series A/B with roller bearing (/3) or ball bearings (/5). Wheels series A with ball bearings (/5), see page 37.

									
Article code	mm	mm	mm	mm	mm	mm	mm	mm	kg
PB 100/34/3 L	100	34	128	105 x 85	80 x 60	9	125		
PB 125/40/3 L	125	40	155	105 x 85	80 x 60	9	150		
PB 125/40/3	125	40	164	135 x 110	105 x 80	11	250		
PB 150/42/3	150	42	194	135 x 110	105 x 80	11	300		
PB 200/50/3	200	50	239	135 x 110	105 x 80	11	400		
PB 100/40/5	100	40	126	135 x 110	105 x 80	11	300		
PB 125/40/5	125	40	164	135 x 110	105 x 80	11	300		
PB 150/50/5	150	50	194	135 x 110	105 x 80	11	400		
PB 200/50/5	200	50	239	135 x 110	105 x 80	11	400		
PB 250/50/5	250	50	290	135 x 110	105 x 80	11	400		

Industrial fixed castors



Industrial swivel castor brackets with a load capacity of up to 400 kg

Housings made of pressed steel, zinc and chromated. Swivel head with double ball bearings, dust and splash proof, with riveted kingpin. Standard type with top plate. ALLSTOP total locking device on the trailing side of the housing, blocks rolling and swivel motion simultaneously.

* with locking device code: PLFZ...

ALLSTOP total locking device
Code: PLF...



single bolt hole
Code: PL.../...R



single bolt hole/total lock
Code: PLF.../...R



directional lock
Code: PL.../...1RIF



foot protection
Code: ...PRO



stem fitting
Code: PLZ...*












PE·VO·LON®

heavy-duty industrial castors











Series WB/5

Series WL/5


								
Article code	mm	mm	mm	mm	mm	mm	mm	kg
WL 080/35/5 L	80	35	118	105 x 85	80 x 60	9	40	300
WL 100/40/5 L	100	40	140	105 x 85	80 x 60	9	45	350
WL 100/50/5	100	50	148	135 x 110	105 x 80	11	50	600
WL 125/40/5 L	125	40	165	105 x 85	80 x 60	9	45	350
WL 125/50/5	125	50	178	135 x 110	105 x 80	11	50	700
WL 150/50/5	150	50	205	135 x 110	105 x 80	11	50	750
WL 175/50/5	175	50	228	135 x 110	105 x 80	11	50	750
WL 200/50/5	200	50	250	135 x 110	105 x 80	11	55	750
WL 250/50/5	250	50	307	200 x 160	160 x 120	15	63	1.000
WL 300/60/5	300	60	347	200 x 160	160 x 120	15	73	1.400

Heavy-duty industrial swivel castors with PEVOLON® wheels

Wheels series A with ball bearings (/5), see page 37.

							
Article code	mm	mm	mm	mm	mm	mm	kg
WB 080/35/5 L	80	35	118	105 x 85	80 x 60	9	300
WB 100/40/5 L	100	40	140	105 x 85	80 x 60	9	350
WB 100/50/5	100	50	148	135 x 110	105 x 80	11	600
WB 125/40/5 L	125	40	165	105 x 85	80 x 60	9	350
WB 125/50/5	125	50	178	135 x 110	105 x 80	11	700
WB 150/50/5	150	50	205	135 x 110	105 x 80	11	750
WB 175/50/5	175	50	228	135 x 110	105 x 80	11	750
WB 200/50/5	200	50	250	135 x 110	105 x 80	11	750
WB 250/50/5	250	50	307	200 x 160	160 x 120	15	1.000
WB 300/60/5	300	60	347	200 x 160	160 x 120	15	1.400

Heavy-duty industrial fixed castors



Industrial swivel castor brackets with a load capacity of up to 1,400 kg

Housings made of strong pressed steel, zinc and chromated. Swivel head with double ball bearings, dust and splash proof. Without kingpin. With grease nipple. ALLSTOP total locking device on the trailing side of the housing, blocks rolling and swivel motion simultaneously.

ALLSTOP total locking device
Code: WLF...



4-way directional lock
Code: WL...4RIF



wheel and directional lock
Code: WLF.../...4RIF



foot protection
Code: ...PRO












PE·VO·LON®

heavy-duty industrial castors









Series TB/5

Series TL/5

								
Article code	mm	mm	mm	mm	mm	mm	mm	kg
TL 080/57/5	80	57	138	135 x 110	105 x 80	11	55	600
TL 100/50/5	100	50	148	135 x 110	105 x 80	11	55	600
TL 125/50/5	125	50	175	135 x 110	105 x 80	11	55	700
TL 150/50/5	150	50	202	135 x 110	105 x 80	11	55	800
TL 175/50/5	175	50	240	135 x 110	105 x 80	11	60	800
TL 200/50/5	200	50	252	135 x 110	105 x 80	11	60	1.000
TL 250/50/5	250	50	300	135 x 110	105 x 80	11	65	1.000

Heavy-duty industrial swivel castors with PEVOLON® wheels

Wheels series A with ball bearings (/5), see page 37.

							
Article code	mm	mm	mm	mm	mm	mm	kg
TB 080/57/5	80	57	138	135 x 110	105 x 80	11	600
TB 100/50/5	100	50	148	135 x 110	105 x 80	11	600
TB 125/50/5	125	50	175	135 x 110	105 x 80	11	700
TB 150/50/5	150	50	202	135 x 110	105 x 80	11	800
TB 175/50/5	175	50	240	135 x 110	105 x 80	11	800
TB 200/50/5	200	50	252	135 x 110	105 x 80	11	1.000
TB 250/50/5	250	50	300	135 x 110	105 x 80	11	1.000

Heavy-duty industrial fixed castors

ALLSTOP total locking device not available for wheel diameter 80 mm.


ALLSTOP total locking device
Code: TLF...



directional lock
Code: TL...TRIF



foot protection
Code: ...PRO



Industrial swivel castor brackets with a load capacity of up to 1,000 kg

Housings made of extra strong pressed steel, zinc and chromated. Swivel head with double ball bearing. Bearing shells made of hardened steel. Kingpin bolted and secured. ALLSTOP total locking device on the trailing side of the housing, blocks rolling and swivel motion simultaneously.

PE·VO·LON®

heavy-duty castors

Series UBC

Series ULC




								
Article code	mm	mm	mm	mm	mm	mm	mm	kg
ULC 125/50/5	125	50	170	140 x 110	105 x 80	13	47	700
ULC 150/50/5	150	50	200	140 x 110	105 x 80	13	55	800
ULC 200/50/5	200	50	245	140 x 110	105 x 80	13	60	1.000
ULC 200/65/5	200	65	255	175 x 140	140 x 105	15	65	1.300
ULC 250/50/5	250	50	305	175 x 140	140 x 105	15	75	1.500
ULC 300/60/5	300	60	355	175 x 140	140 x 105	15	85	2.000

Heavy-duty swivel castors with PEVOLON® wheels

Wheels series A with ball bearings (/5), see page 37.

							
Article code	mm	mm	mm	mm	mm	mm	kg
UBC 125/50/5	125	50	170	140 x 110	105 x 80	13	700
UBC 150/50/5	150	50	200	140 x 110	105 x 80	13	800
UBC 200/50/5	200	50	245	140 x 110	105 x 80	13	1.000
UBC 200/65/5	200	65	255	175 x 140	140 x 105	15	1.300
UBC 250/50/5	250	50	305	175 x 140	140 x 105	15	1.500
UBC 300/60/5	300	60	355	175 x 140	140 x 105	15	2.000

Heavy-duty fixed castors



Precision heavy-duty swivel castor brackets with a load capacity of up to 2,000 kg

Housings in precise highly stable welded steel construction. Swivel head with a high quality thrust ball bearing and a tapered roller bearing for the guidance of the kingpin. All bearing parts dust and splash proof. ALLSTOP total locking device on the non-trailing side of the housing, blocks rolling and swivel motion simultaneously.

ALLSTOP total locking device
Code: ULCF...



4-way directional lock
Code: ULC...4RIF



wheel and directional lock
Code: ULCF...4RIF



foot protection
Code: ...PRO



PE·VO·LON®

heavy-duty castors



Series UB CD

Series UL CD

Article code	mm	mm	mm	mm	mm	mm	mm	kg
ULCD 125/50/5	125	50	180	175 x 140	140 x 105	15	49	1.100
ULCD 150/50/5	150	50	210	200 x 160	160 x 120	15	50	1.600
ULCD 200/50/5	200	50	260	200 x 160	160 x 120	15	60	2.000
ULCD 250/50/5	250	50	320	250 x 200	210 x 160	19	70	2.400
ULCD 300/60/5	300	60	380	250 x 200	210 x 160	19	80	4.000
ULCD 400/110/5	400	110	600	500 x 400	400 x 300	32	120	20.000


Heavy-duty twin wheel swivel castors with PEVOLON® wheels

Wheels series A with ball bearings 1/5, see page 37.
Wheels Ø 400 mm series PAG, see page 38.

Article code	mm	mm	mm	mm	mm	mm	kg
UBCD 125/50/5*	125	50	180	175 x 140	140 x 105	15	1.100
UBCD 150/50/5	150	50	210	200 x 160	160 x 120	15	1.600
UBCD 200/50/5	200	50	260	200 x 160	160 x 120	15	2.000
UBCD 250/50/5	250	50	320	250 x 200	210 x 160	19	2.400
UBCD 300/60/5*	300	60	380	250 x 200	210 x 160	19	4.000
UBCD 400/110/5*	400	110	600	500 x 400	400 x 300	32	20.000

Heavy-duty twin wheel fixed castors

* Plate alignment: long side is parallel with wheel axle.



Precision heavy-duty swivel castor brackets with a load capacity of up to 20,000 kg

Housings in precise highly stable welded steel construction. Swivel head with a high quality thrust ball bearing and a tapered roller bearing for the guidance of the kingpin. All bearing parts dust and splash proof. Wheel locking device on the non-trailing side of the housing.

wheel locking device
Code: ULCDRF...



4-way directional lock
Code: ULCD...4RIF



wheel and directional lock
Code: ULCDRF...4RIF



foot protection
Code: ...PRO












PE·VO·LON®

heavy-duty castors











Series UB PAG

Series UL PAG


								
Article code	mm	mm	mm	mm	mm	mm	mm	kg
UL PAG/150/55/5	150	55	200	140 x 110	105 x 80	11	55	1.750
UL PAG/200/80/5	200	80	280	255 x 200	210 x 160	18	75	4.500
UL PAG/250/80/5	250	80	330	255 x 200	210 x 160	18	80	6.000
UL PAG/300/80/5	300	80	380	255 x 200	210 x 160	18	90	6.000
UL PAG/400/110/5	400	110	530	400 x 300	340 x 240	26	125	12.000

Heavy-duty swivel castors with polyamide wheels

Wheels series PAG with ball bearings (/5), see page 38.

							
Article code	mm	mm	mm	mm	mm	mm	kg
UB PAG/150/55/5	150	55	200	140 x 110	105 x 80	11	1.750
UB PAG/200/80/5	200	80	280	255 x 200	210 x 160	18	4.500
UB PAG/250/80/5	250	80	330	255 x 200	210 x 160	18	6.000
UB PAG/300/80/5	300	80	380	255 x 200	210 x 160	18	6.000
UB PAG/400/110/5	400	110	530	400 x 300	340 x 240	26	12.000

Heavy-duty fixed castors



Precision heavy-duty swivel castor brackets with a load capacity of up to 12,000 kg

Housings in precise highly stable welded steel construction. Swivel head with a high quality thrust ball bearing and a tapered roller bearing for the guidance of the kingpin. All bearing parts dust and splash proof. Wheel locking device on the non-trailing side of the housing.

wheel locking device
Code: UL RF PAG/...



4-way directional lock
Code: UL PAG/...4RIF



wheel and directional lock
Code: UL RF PAG/...4RIF



foot protection
Code: ...PRO

